


Bathymetry compiled by the National Ocean Service (NOS) from bathymetric data collected from 1903 hydrographic survey. This information is not intended for navigational purposes. Government Transverse Mercator Grid (Zone 1, 15000-Meter Table 1-1) are shown inside the mapline. Offshore production areas data compiled or revised by the Minerals Management Service. Hydro lines indicate limits of hard Deep Seismicity Risk Critical Fracture Zones. The projections on this map are not for Federal listing purposes. For such purposes refer to the DOD Official Publication Diagram available from the Minerals Management Service.

EXPLANATION OF BATHYMETRIC DATA

1. Bathymetric contours are shown in black lines. Contour values are in meters. Contour intervals are 10 meters to 200 meters depth, supplemented by 5 meter intervals thence 30 meters to maximum depth, supplemented by 10 meter intervals.

2. Bathymetric contours are shown in black lines. Contour values are in meters. Contour intervals are 10 meters to 200 meters depth, supplemented by 5 meter intervals thence 30 meters to maximum depth, supplemented by 10 meter intervals.



Published at Washington, D.C.
 U.S. DEPARTMENT OF COMMERCE
 NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
 NATIONAL OCEAN SERVICE

1988

BATHYMETRIC CONTOUR INTERVALS: 10 METERS TO 200 METER DEPTH
 SUPPLEMENTED BY 5 METER INTERVALS THENCE 30 METERS TO MAXIMUM
 DEPTH, SUPPLEMENTED BY 10 METER INTERVALS.

DATUM: MEAN LOWER LOW WATER

TRANSVERSE MERCATOR PROJECTION
 Scale 1:250,000

